

SUNMI 80MM Label Printer New



A New Breed of Printer for Smarter Business.

Compatible with
SUNMI DMP



Seamless Scan&Print Solution

Enhance efficiency with an optional barcode scanning module. Our Professional camera supports product entry, QR code payments, and scan for outbound delivery, all in one device.



3-in-1 Printer

Seamlessly integrates three printing modes—Receipt paper, Label paper, and Linerless label—into one device.



*This feature is optional.

Revolutionary one-cable power supply

Industry-first Single-cable power supply patent enables simultaneous power delivery and data communication through a single cable for a clean, tidy countertop.



Innovative Dual Stacking Design *

Doubles operational efficiency while fully freeing up front-desk workspace.



*The Dual Stacking device stand must be purchased separately.

Supports multi-channel transaction printing

Supports Bluetooth / LAN / Wi-Fi / USB / Hyper Wi-Fi* Once connected, it's ready to print instantly upon power-on.



*Hyper Wi-Fi functionality requires customization.

Supports Cloud printing

Integrate via Open API to enable remote printing—enjoy hassle-free cloud printing, no more missed orders.



SUNMI 80MM Label Printer Specs

Product Model NT320	Printer Print Method: Line Thermal Print Resolution: 203*203dpi Print Speed: Up to 150mm/s	CPU MIPS32 1.2GHz	Ports 1*RJ12 Cash Port 1* RJ45 LAN 1*USB2.0 Type-C	Ethernet 100Mbps
Memory RAM: 128MB ROM: 256MB	Audio 1*1W Speaker	Sensor Out of Paper Sensor, Gap Sensor, Open Cover Sensor, Paper Pick-Up Sensor, Cutter Reset, Motor temperature sensor, Head temperature sensor	Characters Per Line Width 80mm: Font A: 48, Font B: 64 Width 58mm: Font A: 33, Font B: 44 Width 40mm: Font A: 21, Font B: 28	Font Type Simplified Chinese (GB18030), Traditional Chinese (BIG5), Japanese (Shift JIS), Korean (KS C 5601), English, Emoji, Global Fonts Library
Paper Size Paper Width: 30mm~80mm Max diameter: 80mm Label Width: 30mm~78mm Label Height: 30mm~150mm Thickness: 0.048mm~0.10mm	Print Command Receipt: ESC/POS Label: TSPL Cloud Communication: MQTT/HTTPS	Power Supply 5V/2A DC	Certification CCC, IC, CE, CB, FCC, WEEE, Rohs, Reach, SRRC	Supported Operating System Windows/Android/iOS/Linux/SUNMI MDM
Dimensions (L*W*H) 130*140*145 mm	Weight 875g	Environment Operating Temperature: 0°C~45°C Operating Humidity: 30%~85% non-condensing Storage Temperature: -20°C~45°C Storage Humidity: 10%~90% non-condensing	Bar Code 1D: UPC-A, UPC-E, JAN13(EAN13), JAN8(EAN8), CODE39, Code 2 of 5 Interleaved, CODABAR, CODE93, CODE128, Code 2 of 5 Matrix, Code 2 of 5 Industrial, Code 2 of 5 IATA, Code 2 of 5 Datalogic, CODE11, CODE39 Extended, GS1 DataBar, GS1 DataBar Expanded, MSI Plessey 2D: PDF417, QR code	

Normal Version

Scanner Version

Wi-Fi Version

Linerless Version

Wi-Fi	/	/	Wi-Fi6 5GHz/2.4GHz IEEE 802.11 a/b/g/n/ac/ax	Wi-Fi6 5GHz/2.4GHz IEEE 802.11 a/b/g/n/ac/ax
Bluetooth	/	/	Bluetooth 5.4, Support BLE	Bluetooth 5.4, Support BLE
Paper Type	Receipt , Label	Receipt , Label	Receipt , Label	Receipt , Label , Linerless
Life	Print Life: 150km (Receipt) , 50km (Label) Cutter Life: 1000000 (Receipt) , 500000 (Label)	Print Life: 150km (Receipt) , 50km (Label) Cutter Life: 1000000 (Receipt) , 500000 (Label)	Print Life: 150km (Receipt) , 50km (Label) Cutter Life: 1000000 (Receipt) , 500000 (Label)	Print Life: 150km (Receipt) , 50km (Label,Linerless) Cutter Life: 1000000 (Receipt) , 500000 (Label,Linerless)

Reading Precision: 1D: ≥4mil (code128)

2D: ≥7.5mil (QR Code)

Symbologies: 1D: UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Industrial 2 of 5, Codabar, MSI, Matrix 2 of 5, GS1 DataBar

2D: QR Code, Data Matrix, PDF417, Aztec

Scanner

/ / /